


INTEGRATED PRODUCT

Manually Adjustable Low Pulsation Micro Pump Unit





Suitable for Lab-on-a-Chip Devices, Cell Culture Media Circulation, etc.

Features

- Flow from a piezoelectric micro pump is adjusted by a micro needle valve.
- Can adjust flow from nl/min level to around 1.5 ml/min manually.
- Flow pulsation at low flow rates is drastically reduced by a micro needle valve (See the graph at the bottom).
- Usable as a stand alone by AAA or R03 batteries.
- Compact size: Dimensions of 70 x 25 x 94 mm
- Maximum pump pressure is around 35 kPa (The value varies depending on the flow channel configuration and fluid characteristics).


Demonstration video is available at the following website.
http://www.takasago-elec.co.jp/movie/low_pulsation_pump_unit-e.wmv

Flow Characteristics <Example flow data>



Reduction of Flow Pulsation

<Example flow data>



Similar Item



Unit of a piezo pump and a needle valve is also available (Either a driver or a controller is separately needed).

Note: Details including specifications may change without notification.

TAKASAGO ELECTRIC, INC.

66 KAKITSUBATA, NARUMI-CHO, MIDORI-KU, NAGOYA, 458-8522 JAPAN

Tel +81-52-891-2301 Fax+81-52-891-7386

E-mail: info@takasago-elec.co.jp URL: <http://www.takasago-fluidics.com/>